

ODYSSEY[®]

BATTERY

625-DIN C-1500

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for Marine engine start and deep-cycle use

Power & Performance

| | |
|--|----------|
| Voltage | 12V |
| Capacity (20-hour rate) | 220Ah |
| Capacity (10-hour rate) | 198Ah |
| Cold Cranking Amps (CCA, SAE J537) | 1500A |
| PHCA - 5-second pulse current | 2700A |
| HCA | 2015A |
| MCA | 1787A |
| Reserve capacity | 475 mins |
| Short circuit current (using IEC method) | |
| Internal resistance at 20°C (using IEC method) | |



Dimensions & Weight

| | |
|------------------------------|---------|
| Length | 518 mm |
| Width | 276 mm |
| Height (to top of terminals) | 225 mm |
| Height Container | 215 mm |
| Weight | 64.9 kg |

Temperature

| | |
|-----------------------------|----------------|
| Operating Temperature Range | -40°C to +50°C |
| Optimum Storage Temperature | +20°C |

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.


Charging & self-discharge

| | |
|-----------------------------------|----------------|
| Type of charging curve | IUU |
| Charge voltage @+20°C | 14.4V to 14.8V |
| Self-discharge per month at +20°C | 1.25% |
| Self-discharge per month at +40°C | 5% |

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted.
2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first.
Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

Terminal Position



Terminal Type

SAE Terminals

