DOMETIC CFX3 75DZ

MOBILE DUAL-ZONE COMPRESSOR COOL BOX AND FREEZER, 65 L



POWERFUL COOLING ADJUSTABLE TEMPERATURE

STAY CONNECTED VIA CFX3 APP ROBUST BUILT FOR OUTDOORS

YEARS OF INNOVATION FOR COOLING PERFECTION

This ultimate powered cool box produces seriously impressive cooling, allowing you to bring more of the food and drinks you love wherever you go. Its robust design is built for tough outdoor use, while a convenient mobile app puts the control of your Dometic CFX3 at your fingertips. Dual zone storage compartments have independent temperature control which enables simultaneous cooling and freezing.

Take control of outdoor adventures like never before with the Dometic CFX3 75DZ. Enjoy fresher food at your fingertips thanks to Dometic's market leading VMSO3 variable speed compressor with optimised software for better cooling, freezing and power consumption. The CFX3 features durable fender frames that protect the edges of the cool box, making it ideal for rugged trips. Strong, spring-loaded aluminium handles make it easy to lift and carry. Set the cooling temperature of your CFX3 on the TFT display screen and pack all your favourite foods. Download the CFX3 app and roam free from worry. Once your CFX3 is connected through your phone, you can set the ideal temperature, and get a detailed history of energy and temperatures. We also offer a range of accessories to get the most out of your cool box, including a durable insulated protective cover.

SPECIFICATIONS

GENERAL

Model CFX375DZ

SKU number 9600025333 SKU replaced by 9600029532 Model on label CFX375DZ

Product Description Mobile dual-zone compressor

cool box and freezer, 65 l Single or Dual Zone Dual

Scope of delivery 1 cooler, 1 manual, 1 Connection cable for 12/24V connection, 1 Connection cable for 100-240V connection, removable wire baskets

Refrigeration technology Compressor

DIMENSIONS

Dimensions product depth 495 mm Dimensions product height 472 mm Dimensions product width 892 mm

Net weight 27.8 kg

Gross volume (EN62552) 741

Storage volume - total (EN 62552) 651

ELECTRICAL

Input voltage (AC) 100-240 V Input voltage (DC) 12/24 V Input frequency 50/60 Hz

Rated input current (AC) 1.12A at 100V, 0.47A at

240V A

Rated input current (DC) 9.6 A Rated input power (AC) 59 W

PERFORMANCE

Climate class (EN62552) N/T

Energy class EU (1060/2010/EC) A+

Energy Consumption 12VDC

(Internal@Large4C/Small-15C, Ambient@32C)

3.04 Ah/h

Energy Consumption 12 V DC (Ambient@90 °F,

Internal@39 •F) 1.43 Ah/h Hermetically Sealed True Refrigerant, type R134a

GWP 1430

Refrigerant amount 59 g **CO2 equivalent** 0.084 t

Insulation Type PU (Polyurethane) **Insulation Thickness** 55 mm

Insulation I hickness 33 mm

Average energy consumption at AC (EN62552) 0.2956 kWh/24h

ADDITIONAL

Anti-condensation coil Yes

Connectivity Type Bluetooth, WiFi **Cable length supply cable** 2 m

USB Port 5V, 2A

Interior light Yes, LED

Basket Yes Drain plug Yes

