盟HOUGHTON

Belaire Range of

Mobile Air-Conditioners

T3500



Powerful performance for larger motorhomes, caravans and boats. Features a low plenum that suits free discharge or ducted air distribution systems.

Features:

- 1. Low plenum with an elegant design that complements modern interiors. Features easy to read LED display showing temperature and mode.
- 2. Attractive streamlined canopy design to perfectly integrate with modern caravan, motorhome and boat design carriage return.
- 3. Remote control with cooling, heating, dehumidifying, dry, sleep and timing functions.
- 4. Three speed ultra-quiet, high efficiency indoor fan. The large outdoor axial fan draws air to exchange heat, leading to highly efficient, powerful performance.
- 5. Patented technology provides thermal protection for the evaporator.
- Spiral retractable duct allows easy installation without cutting. Insulation eradicates condensation while optimizing power and performance.
- 7. Excellent reverse cycle performance allows the T3500 to operate in temperatures as low as -5°C and up to +50°C. Features intelligent defrosting technology.







Specification:

| Power supply | 220-240V/50Hz | Maximum input power | 1500W |
|---------------------|--------------------|---------------------------|-----------------------------|
| Refrigerant charged | R410A/590g | Maximum current | 6.5 A |
| Cooling capacity | 3500W (11,935 BTU) | Maximum air flow | 318 CFM |
| Heating capacity | 3500W | Installed Weight | 35.5+2.8 (kg) |
| Power input cooling | 1300W | Installation opening (mm) | 360 x 360 (Optional adapter |
| Power input heating | 1200W | | required for 400 x400) |
| Current cooling | 5.6 A | Outdoor unit dimension | 340 x 680 x 998 |
| | | H x W x L (mm) | |
| Current heating | 5.2 A | Plenum unit dimension | 43 x 536 x 557 |
| | | H x W x L (mm) | |